

TRACK CHIPPER

6" Capacity, Hydraulic Feed

Salsco, INC.
LEADER BY DESIGN



**MADE IN
THE U.S.A.**

Why drag the brush to the Chipper? The self propelled 6" round wood capacity Track Chipper can go almost anywhere. At just 35" wide, it will fit through most back yard gates and go through the thickest woods. Rubber tracks will drive the Track Chipper up or down most any hill and will not damage driveways, sidewalks and lawns. The 360° Hand Crank Rotation and Height Adjustable Exhaust Chute is standard equipment. The Track Chipper Transport Trailer is equipped



with a Torflex axle, heavy duty diamond plate fenders with light enclosures, flag holders and fully approved D.O.T. LED lighting package. Powered by either a 37HP Briggs & Stratton E.F.I. engine or a 40HP Kohler engine. Both with a full muffler guard and a rain guard. Engines are equipped with a full panel, including a hot oil shutdown.



The Go Anywhere Chipper!



Extra wide infeed hopper and 12" wide x 6" high infeed opening easily handles brushy material & branches up to 6" round.



Drive controls with neutral safety locks are mounted to the side and are easily accessed by the operator.



Speed Sensing is optional and monitors the RPM of the impeller and is equipped with a Safety Stop Button.



The impeller housing is equipped with an electric safety switch feature. The engine will not start if the impeller housing is not closed and securely pinned.



360° Hand Crank Exhaust and Height Adjustable Exhaust Chute is standard. Direction of debris is easily adjusted.

Salsco, INC.
LEADER BY DESIGN

Quality of Workmanship, Innovative Design, Built to Last!

SPECIFICATIONS - Track Chipper	
ENGINE OPTIONS:	37HP Briggs & Stratton, E.F.I. gas, electric, 40HP Kohler gas, electric.
FUEL TANK:	7" x 31-7/8" x 22" steel tank. 20.5 gallon capacity, with lockable filler cap with dip stick.
BATTERY:	12 volt, CCA 650, automotive type, lockable box.
CLUTCH:	Centrifugal clutch, size 6 type P
EXHAUST CHUTE:	360° hand crank, height adjustable exhaust chute with easy adjust exhaust directional flap.
INFEED OPENING:	6" high x 12" wide opening at the infeed.
INFEED TRAY:	Extra wide, 57" wide x 33" high, 1/4" thick steel plate sides, with fold down infeed tray. Control bar positioned at top of infeed tray to control movement of the feed roll. High speed, low speed, neutral & reverse.
FEED ROLL:	One (1), 7" long x 12" diameter, weighted, replaceable blades, fully welded.
IMPELLER HOUSING:	1/4" thick steel, impeller housing is vented to provide more air flow for chip exhaust. Electric safety lock.
IMPELLER:	Fully balanced, 1" thick x 26" diameter steel impeller with four (4) welded and gusseted exhaust paddles. 200 lbs. (Approximately)
CHIP BLADES:	Four (4), 1/2" thick x 5" long x 4" wide, double-sided.
BED KNIVES:	Two (2), one horizontal, one vertical. Both are 1" thick steel, replaceable, sharpenable & adjustable
BEARINGS:	4-bolt, heavy duty, cast iron, greaseable & self-centering.
HYDRAULIC COMPONENTS:	Hoses - SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. Motors - Two (2), Char-Lynn 29.4 displacement, one (1) Char-Lynn 17.9 displacement. Pump - Hydro-Gear, variable speed piston type tandem pump.
HYDRAULIC TANK:	7" x 18" x 10-7/8" steel tank. 4.6 gallon capacity, with lockable filler cap with dip stick.
FRAME:	Single piece welded box construction, 3/8" plate.
TRACKS:	Two (2), Bridgestone rubber tracks.
OPTIONS:	Speed sensing.
PAINT:	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
DIMENSIONS:	Width: 2' 9", Height: 7' 6", Weight: 3,960 lbs. (approximately)
SPECIFICATIONS - Transport Trailer	
AXLE:	3,500 lb. Torflex axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other.
TIRES/WHEELS:	Two (2), ST225/80R16 LR "E", 10 Ply.
TONGUE:	2" x 3" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate bracket with 1/4" gussets.
HITCH:	Adjustable height hitch. 2-5/16" ball or 3" pintle coupler.
JACK:	Side wind swivel snap ring mount jack. 2,000 lb. lift capacity.
LOCKING PIN:	Locking pin to accommodate 3" pintle coupler, welded to the chipper.
FENDERS/LIGHTS:	Extra heavy duty 1/4" thick diamond plate fenders with safety light guards. LED light package, D.O.T. approved.
FRAME:	Welded structural steel. 3" x 2" x 1/4" wall rectangular steel tube, continuous welds for strength and gusseted where needed.
PAINT:	Polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
DIMENSIONS:	Width: 5' 9" Length: 10' Weight: 800 lbs. (Approximately) GVWR - 5,200 lbs.

Specifications & Options Subject to Change Without Notice

Rev. 10-1-2022

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries
3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills



105 Schoolhouse Road
Cheshire, CT 06410 U.S.A.
800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com